

# ROYAL OIL CO.

SPECIALTY LUBRICANTS

## E-LIMINATOR H2O

**PREMIUM WATER REMOVER**

**Captures and Disperses Water in Fuel**

**Prevents Water Freezing in Fuel Lines**

**Microbial Growth Prevention**

**Prevents Rust and Corrosion**

**Used in a Wide Variety of Fuel Types**

Water contamination is always a battle. A crucial step in a proper fuel management program is to minimize or eliminate water in fuel. Therefore, Royal developed E-LIMINATOR H2O.

Ultra-Low Sulfur Diesel and Biodiesel ultimately have more water contamination. Moisture in the atmosphere condenses on interior walls of fuel tanks, and over time, settles to the bottom. E-LIMINATOR H2O resolves these issues when water becomes excessive.

E-LIMINATOR H2O can be used with Ultra Low Sulfur Diesel, High Sulfur Diesel, Biodiesel, Kerosene, Gasoline and Ethanol Gasoline.

*“With the invention of fuel storage, the introduction of water contamination immediately followed. Water E-LIMINATOR H2O will solve water issues in fuel storage and vehicle tanks. It is a versatile product able to be used with a variety of fuel types.”*



# E-LIMINATOR H2O

## Product Specifications

Test Description	Typical Properties
API Gravity	25.1
Density, lb./gal @60 deg F	7.53
Flash Point, PM, deg F and C	154°F/67°C
Color	Colorless

### DIRECTIONS:

Royal Oil Co. recommends draining or pumping out as much free-standing water as possible in the bottom of the tank before adding E-LIMINATOR H2O Water Remover.

For initial use treat 1 gallon of water to 1 gallon E-LIMINATOR H2O. This will absorb 1 gallon of water. Do not treat more than 1 gallon E-LIMINATOR H2O to 100 gallons of fuel.

For storage tank maintenance, treat at 1 gallon E-LIMINATOR H2O to 3,000 gallons of fuel.

For vehicle or semi-truck tank maintenance, add 1 quart to 750 gallons of fuel, 1 pint to 375 gallons of fuel and 1 ounce to 25 gallons of fuel every three months.

E-LIMINATOR H2O should be added to the storage tank first, then add fuel to assure complete dispersion of the product. If needed, you can re-circulate the fuel to mix E-LIMINATOR H2O throughout.

**E-LIMINATOR H2O complies with the federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.**

Sharing lubricant knowledge and delivering the highest quality products, two things we promise our customers. The difference will change how you view, purchase and utilize greases and oils from here forward.

*Family owned and operated since 1926.*



PRINTED IN U.S.A. 2020  
R10227

842 N. Main St.  
Fort Worth, TX 76164  
(800) 332-1926  
sales@royaloilus.com  
www.royaloilus.com

