

ROYAL OIL CO.

SPECIALTY LUBRICANTS

EFT 2550

Emergency Fuel Treatment

Fast Acting

Liquifies Gelled Fuel

De-Ices Frozen Filters/Lines

100% Safe for Fuel Systems

Diesel, Bio or Kerosene Blends

Easy To Use

“Nothing is worse for an equipment operator in severe cold weather than to have a gelled fuel system or iced lines and filters. Immobilized equipment is costly and an issue that requires time and energy. EFT 2550 is a ‘must keep on the shelf’ product.”

Once diesel fuels or diesel fuel blends reach their CFPP (Cold Filter Plug Point), issues have already arrived. A gelled fuel system will shut down an operation, costing time, money and resources.

While we highly recommend introducing DSL-MAX to any fuel system, due to its exceptional ability to increase cold weather performance among other benefits, we realize there are times when untreated or undertreated fuel will leave you needing assistance.

EFT 2550 (Emergency Fuel Treat) was designed to act quickly, by dissolving gelled fuel and iced lines and filters. In a matter of minutes EFT 2550 can have fuel flowing again and equipment firing up and ready to run. EFT 2550 is effective with bio-blended diesel fuels and kerosene blends. Easy to use and with an excellent storage life, EFT 2550 is a product to purchase and hold onto. Consider this insurance for your business or operation of you live in climates where the temperatures can drop and drop quickly.



EFT 2550

INSTRUCTIONS FOR EMERGENCY TREATMENT

1. Remove fuel filter
2. Drain any and all remaining liquid from filter
3. Add EFT 255- to fuel filter receptacle until full
4. Reinstall fuel filter
5. EFT 2550 must be added to equipment fuel tanks at the ratio of 1 quart to 25 gallons. (Less severe situations can use a ratio of 1 quart of EFT 2550 to every 50 gallons of fuel)
6. Wait 15 minutes to allow EFT 2550 to work before starting engine. If engine is sluggish or will not start, wait another 15 minutes.
7. Start engine and let idle 5 minutes before returning to full operation.
8. As a Preventative maintenance to prevent such roadside emergency, winterize your fuel with DSL-MAX or DUAL Gard 12.

PRODUCT SPECIFICATIONS

API Gravity @ 600°F.	30
Flash Point, °F.	95

Sharing lubricant knowledge and delivering the highest quality products, two things we promise our customers. The difference will change how you view, purchase and utilize greases and oils from here forward.

Family owned and operated since 1926.



842 N. Main St.
Fort Worth, TX 76164
(800) 332-1926
sales@royaloilus.com
www.royaloilus.com

