

ROYAL OIL CO.

SPECIALTY LUBRICANTS

SUPER-SEALER

Economical Blacktop Repair

Fast & Easy to Use

Ready for Traffic in Hours

Seals Out Damaging Moisture

Environmentally Friendly

Durable in All Climates

SUPER-SEALER is a unique blend of an asphalt emulsion, mineral fillers, glass fiber, ground rubber and plasticizers designed especially for aging alligatored areas on asphalt parking lots. It is also used for filling cracks in excess of 1/2 inch in width.



APPLICATION

Coverage up to 20 Sq. Ft. for patching alligatored areas and up to 150 linear feet of 1/2 inch x 1/2 inch depth cracks, per gallon. (Coverage will vary, depending on size and frequency of cracks in alligatored areas.) A second application of Cold Flow Sealer will give cosmetic benefits in terms of smooth, consistent appearance and will help hide the outline of cracks in the alligatored area.

SUPER-SEALER can be used in conjunction with Royal's SEAL-TITE asphalt coating. Inquire how.

SUPER-SEALER

Product Specifications

Color	Black
Odor	Bland Asphaltic
Weight per gallon @ 77°F. ASTM D1010, (lbs.)	9.60 ± 0.20
Nonvolatile %, ASTM D2939	70.00-72.00
Viscosity @ 77°F, ASTM D562 (Krebs stormer Unit)	125 min.
Penetration (0.1 mm), ASTM D5	Pass
Resistance to Water, ASTM D2939	No blistering, no re-emulsification
Ductility, 77°F 5 cm/min. cm, ASTM D113	Pass
Flammability	Non-flammable
Shelf Life (Years)	1-2
Cure Time	Dries for traffic in 2-4 hours in normal conditions; cures completely in 24 hours.
Minimum Application Temperature	+50 °F (DO NOT apply when rain or frost is forecast within 12 hours.)
Application	Cold applied with squeegee
Clean-up	Water and soap.... Or solvent, if material has set-up
Handling:	Do not allow to freeze or be exposed to temperatures above 100 °F. Do not store in direct sunlight. Container should be sealed when not in use. Keep out of reach of children.

Sharing lubricant knowledge and delivering the highest quality products, two things we promise our customers. The difference will change how you view, purchase and utilize greases and oils from here forward.

Family owned and operated since 1926.



842 N. Main St.
Fort Worth, TX 76164
(800) 332-1926
sales@royaloilus.com
www.royaloilus.com

