

ROYAL OIL CO.

SPECIALTY LUBRICANTS

X-TREME STABILIZER

Effective, Multi-functional, Premium Oil Additive

Synthetic Blend

Industry Best Base Oils

Excellent Film Strength

Boosted Anti-Wear

Clean/Keep Clean Chemistry

Extended Drain Capability

Exceeds Industry Specs



X-TREME STABILIZER is a jack of all trades kind of product. It can be added to any petroleum product including motor oils, gear lubricants, hydraulic fluids and transmissions fluids to help maintain the fluids film strength and increase lubricity.

X-TREME STABILIZER is a viscosity booster which in turn helps prevent metal to metal contact from occurring. The product contains a microscopic polymer that is crucial to assisting in the original fluids performance in cold and hot environments. The polymer will increase the fluids viscosity in cold temperatures allowing it to flow more efficiently, while also inhibit the oil molecules from thinning in hotter temperatures.

X-TREME STABILIZER will extend the life of the fluid it is added to, which will ultimately lower your expense on repairs and downtime due to lubricants breaking down.

“Building a better engine oil is a choice. Quality materials, time and care make a superior product, its your equipment and bottom line that benefit.”

X-TREME STABILIZER

Product Specifications

MIXING RATIOS

Engine Oils:	2 1/2% up to 10%, or 4 oz. up to 16 oz. to 5 quarts of oil
Transmissions, Gears, & Hydraulics:	1% up to 5%, or 3 or 4 oz. up to 16 oz. to 10 quarts of oil
For Wet Brake Systems:	1% to 2% or 3 to 6 oz. to 10 quarts of oil (Not suggested with a Poly alkaline Glycol Based Synthetic)

TYPICAL ANALYSIS

Viscosity @ 40 °C, cSt	1500
Pour Point, °F.	-5
Flash Point, °F.	165
Specific Gravity	.87
Weight/Gallon	7.25

Sharing lubricant knowledge and delivering the highest quality products, two things we promise our customers. The difference will change how you view, purchase and utilize greases and oils from here forward.

Family owned and operated since 1926.



842 N. Main St.
Fort Worth, TX 76164
(800) 332-1926
sales@royaloilus.com
www.royaloilus.com

